

NEW ENCLOSED DRY PRIME TRASH PUMP **PACKED WITH VALUE**

Model MTP 6500FH



Front Hood - Access to
Daily Operator Checks

Back Hood - Access
to Pump and Inlet

New Patent Pending Flip-Hood Design



6" Inlet



Analog Gauge Control
Panel - Lockable Cabinet



6" Discharge End

Great Return on Investment

- New Flip-Hood Enclosure Design
- Sound Attenuated for Residential Areas
- Lockable for On-Site Security
- Protection from Weather Elements
- 110 Gallon Fuel Tank
- Over 30 Hour Run Time
- Auto Start/Stop Controls
- Handles up to 3" Solids

Easy To See • Easy To Use • Easy To Service



For more information contact:

Tele: 800-926-9768 Email: sales@m-p-llc.com

Or visit: www.m-p-llc.com

Packed With Power

MTP 6500FH Enclosed Dry Prime Trash Pump Specifications

ENGINE

- John Deere PE5030TF270, 5 cylinder diesel engine
 - 57 HP continuous
 - 67 HP intermittent
 - 110 gallon fuel tank
 - 2.8 gallons per hour
 - 34 hour maximum run time
 - Electric start

PUMP

- Self-priming centrifugal pump
 - 6 inch
 - Flows up to 2,450 GPM
 - Heads up to 145'
 - Maximum solid size: 3"
 - Impeller material – High chrome cast iron
 - Max. lift suction 28'
 - Single mechanical seal with silicone carbide seal faces
 - Ductile iron (ASTM A536) volute and wear plates

CONTROLS

- Analog gauge panel
 - Oil pressure
 - Temperature
 - Fuel level
 - Volts
 - Engine RPM
- Automatic shut downs for
 - Low oil pressure
 - High water temperature
 - Overspeed
 - Overcrank
- Emergency STOP button
- Remote input start/stop controls –compatible with dual float system

ENCLOSURE

- Sound attenuated aluminum enclosure with white industrial powder coat finish

Trailer Mounted Weights & Dimensions :

Dry weight: 3,462 lbs Size: 150"l x 57"w x 74"h

ENCLOSURE

- “Flip-Hood” design
 - Easy access for daily maintenance
 - Centralized location of all electrical connections and wiring
- 70dB(A) @ 23 feet @continuous power
- Fully lockable enclosure
- Emergency stop switch located on outside of enclosure
- Locking external fuel cap
- Central lifting point on steel internal lifting structure
- Skid mounted for easy mounting to trailer or base

TRAILER

- “Flip-Tongue” design
 - Allows up to 12 units per truckload- single axle
 - Allows up to 10 units per truckload- tandem axle
 - Saves freight costs/lot space
- Industrial powder coated flat black finish
- Tie down points on unit
- Tail, side, brake, and directional lights meet DOT standards
- One 5000 lb. axle w/surge brakes
- Highway approved ST225/75R15 tire:
- Safety chains
- 2" ball hitch
- 3,000lb. capacity top-wind tongue jack with footplate
- 2-(2,000lb) side-wind jacks

OPTIONS

- Dual float system

WARRANTY

- 1 year unlimited hours, 2 years 2000 hours on unit
- 1 year unlimited hours, 2 years 2000 hours from John Deere



For more information contact:

Tele: 800-926-9768 Email: sales@m-p-llc.com

Or visit: www.m-p-llc.com