

## Packed with Value

### Reliable

- Strong performer in shallow, high solid conditions
- Auto priming intermittent pumping
- Limitless dry run without damage

### Easy to Use

- Simple design/low maintenance
- Large opening flap valves
- Self cleaning water flow

### Wear Resistant

- Durable cast aluminum parts
- Enclosed gears in oil bath

### Compact style

- Easily maneuverable



The 5537WT diaphragm pump is ideal for low volume/head conditions such as seepage dewatering, and sandy, muddy, or sludgy waters of shallow construction areas, trenches, and excavation sites. Dependable performance for pumping industrial waste, marine tanks and cleaning septic systems.

Specifications	MCP5537WT
<b>Fluid :</b>	
Pump Output Capacity gpm (Lpm)	85 (322)
Max. Discharge Head ft (m)	25 (8)
Max. Lift Suction ft (m)	25 (8)
Max. Operating Speed (rpm)	2800
<b>Pump:</b>	
Make / Model	CH&E / 5537 AL
Fitting Size (in)	3 NPT
Suction/ Discharge Connection	3 NPT
<b>Engine:</b>	
Brand	Honda
Model	GX120
Output Maximum hp (kW)	4.0 (2.9)
Engine Rated Speed (rpm)	3600
Fuel Tank Capacity gal (L)	.66 (2.5)
Maximum Run Time hrs	2.3
Starting Method	recoil
<b>Dimensions:</b>	
Wheel Mounted (l x w x h)	40 x 29 x 24
Dry Weight lbs (kg)	126 (57.1)

Specifications or design are subject to change without notice  
 WARNING: Do not use in explosive atmosphere or for pumping volatile flammable liquids

